

## CARBON DIOXIDE TRANSMITTERS CDT-MOD-2000 SERIES

Multifunctional, wall mount CO<sub>2</sub> transmitters for building automation systems that use Modbus serial communication protocol

The CDT-MOD-2000 series air quality transmitters are engineered for building automation systems in the HVAC/R industry. The CDT-MOD-2000 series measures carbon dioxide (CO<sub>2</sub>), utilizing the industry standard NDIR measurement principle, and temperature (T). Optional relative humidity (rH) measurement is also available in the same device. The CDT-MOD-2000 series devices have large touchscreen display making the configuration of the device quick and easy. Configuration is also possible via Modbus network.

The CDT-MOD-2000 series transmitters calibrate themselves automatically using ABC™ logic. The ABC™ logic requires that the space in which the transmitter is used needs to be unoccupied for four hours per day so that the indoor CO<sub>2</sub> concentration drops to the outside level. CDT-MOD-2000-DC is a dual channel model with a measuring channel and a reference channel that makes a continuous comparison and the necessary adjustment accordingly. CDT-MOD-2000-DC is also suitable for buildings that are continuously occupied.

### CDT-MOD-2000 series devices include:

- Separate field configurable Modbus output for each measurement parameter (CO<sub>2</sub>, rH, T)
- Offset feature enabling field calibration for each measurement parameter (CO<sub>2</sub>, rH, T)
- One analog output for selected measurement: voltage (0/2–10 V) or current (4–20 mA)
- 2" x 3" touchscreen display
- Optional relay output

### APPLICATIONS

CDT-MOD-2000 series devices are commonly used to monitor:

- CO<sub>2</sub> and humidity levels in offices, public spaces, meeting rooms and classrooms
- CO<sub>2</sub> levels of return air in ventilation systems
- incoming air and return air humidity levels in ventilation system
- humidity in various industrial applications
- temperatures in HVAC/R environment
- CDT-MOD-2000-DC series devices can also be used in applications where there is a constant source of carbon dioxide present (for example hospitals and greenhouses)



### MODEL SUMMARY

CDT-MOD-2000			CDT-MOD-2000-rH		
Description	Model	Product code	Description	Model	Product code
Carbon dioxide transmitter for room with Modbus configuration and display	CDT-MOD-2000-D	301.001.004	Carbon dioxide and humidity transmitter for room with Modbus configuration and display	CDT-MOD-2000-rH-D	301.003.004
- with relay	CDT-MOD-2000-1R-D	301.001.005	- with relay	CDT-MOD-2000-1R-rH-D	301.003.005
- with dual channel sensor	CDT-MOD-2000-DC-D	301.005.003	- with dual channel sensor	CDT-MOD-2000-DC-rH-D	301.006.003
- with dual channel sensor and relay	CDT-MOD-2000-DC-1R-D	301.005.004	-with dual channel sensor and relay	CDT-MOD-2000-DC-1R-rH-D	301.006.004

# CARBON DIOXIDE TRANSMITTERS

## CDT-MOD-2000 SERIES

### SPECIFICATIONS

#### Performance

##### Measurement ranges:

CO<sub>2</sub>: 400–2000 ppm

Temperature: 0...50 °C

Relative humidity: 0–100 %

##### Accuracy:

CO<sub>2</sub>: ±40 ppm + 2 % of reading, DC model: 75 ppm or 10 % of reading (whichever is greater)

Temperature: <0.5 °C

Relative humidity: ±2...3 % at 0...50 °C and 10–90 % rH

Total error band includes accuracy, hysteresis and temperature effect over 5...50 °C and 10–90% rH.

#### Technical Specifications

##### Media compatibility:

Dry air or non-aggressive gases

##### Measuring units:

ppm, °C and % rH

##### Measuring element:

CO<sub>2</sub>: Non-dispersive infrared (NDIR)

Temperature: Pt1000 (models without rH-measurement)

Integrated (models with rH-measurement)

Relative humidity: Thermoset polymer capacitive sensing element

##### Calibration:

Automatic self-calibration ABC Logic™ or continuous comparison (DC)

##### Environment:

Operating temperature: 0...50 °C

Storage temperature: -20...70 °C

Humidity: 0 to 95 % rH, non condensing

#### Physical

##### Dimensions:

Case: 99 x 90 x 32 mm

##### Weight:

150 g

##### Mounting:

3 screw holes slotted, 3.8 mm

##### Materials:

Case: ABS

##### Protection standard:

IP20

##### Display (Optional):

Touchscreen

Size: 77.4 x 52.4 mm

##### Electrical connections:

Power supply:

5-screw terminal block

(24 V, GND)

0.2–1.5 mm<sup>2</sup> (12–24 AWG)

Relay out:

3-screw terminal block

(NC, COM, NO)

0.2–1.5 mm<sup>2</sup> (12–24 AWG)

#### Electrical

##### Input:

24 VAC or VDC, ±10 %

Current consumption: max 90 mA (at 24 V) +

10 mA for each voltage output or 20 mA for

each current output

Relay out:

SPDT Relay, 250 VAC / 30 VDC / 6 A

Adjustable switching point and hysteresis

One analog output for selected media:

0/2\*–10 VDC, Load R minimum 1 kΩ

\*(2–10 VDC display models only) or

4–20 mA, maximum load 500 Ω

#### Communication

Protocol: MODBUS over Serial Line

Transmission Mode: RTU

Interface: RS485

Byte format (11 bits) in RTU mode:

Coding System: 8-bit binary

Bits per Byte:

1 start bit

8 data bits, least significant bit sent

first

1 bit for parity

1 stop bit

Baud rate: selectable in configuration

Modbus address: 1–247 addresses selectable in configuration menu

#### Conformance

Meets requirements for CE marking:

EMC Directive 2014/35/EU

RoHS Directive 2011/65/EU

LVD Directive 2014/35/EU

WEEE Directive 2012/19/EU

**COMPANY WITH  
MANAGEMENT SYSTEM  
CERTIFIED BY DNV GL**  
= ISO 9001 = ISO 14001 =



### HOW TO GENERATE A MODEL?

Example: CDT-MOD- 2000-1R-D	Product series				
	CDT2000	Carbon dioxide transmitter, analog configurations			
	CDT-MOD-2000	Carbon dioxide transmitter, Modbus configuration			
		Calibration			
			ABC logic™, Automatic Background Calibration		
		-DC	Dual channel, for continuously occupied space		
			Mounting		
			Wall mount		
			Relay		
			-1R	With relay	
				Without relay	
				Relative humidity sensor	
			-rH	With relative humidity sensor	
				Without relative humidity sensor	
				Display	
				-D	With display
					Without display
Model	CDT-MOD-2000		-1R		-D