

DFA-T , DFC- T(old model:LZM-ZT)

mIPm Series Acrylic Flow Meter

The series flowmeter is clear viewing type with SS valves to adjust the flow rate in a large measuring range .It is featured in a beautiful look and easy installation

Technical Parameters of DFA-ATseries Flow Meter

Model	Measure Range			Screw thread	Accuracy
	GPM (Liquid)	LPM (Liquid)	Nm ³ /h (Gas)		
DFA-15AT		15-150LPH	0.1-1 0.16-1.2 0.3-3 0.4-4	Male1/2" Female 1/4" BSP/NPT	±4%
DFA-15T		10-100LPH	0.6-6 1-10 1.6-16 2.5-25 4-40		
		16-160LPH			
		25-250LPH			
	0.1-1	0.5-4			
	0.2-2	1-7			
	0.3-3	1-11			
	0.5-5	2-18			
DFA-25T	2-10	10-35	6-60 20-100 40-160 50-250 35-350	Male1" BSP/NPT	
	4-14	15-50			
	6-20	20-70			
	10-35	30-130			
	10-40	30-150			
	15-45	50-170			



Please forward to Page for more information of DFA series.

Technical Parameters of DFC-T series Flow Meter

Model	Measure Range			Screw thread	Accuracy
	GPM (Liquid)	LPM (Liquid)	Nm ³ /h (Gas)		
DFC-15T	0.1-1	0.5-4	1-10 1.6-16 2.5-25 4-40	Male 1/2"NPT 1/2"BSP	±4%
	0.2-2	0.8-8			
	0.3-3	1-11			
	0.5-5	2-18			
	1-7	2-28			
	1.5-9	5-35			
DFC-20T	2-10	8-40	2.5-25 6-60 16-80 16-160	Male 3/4"NPT 3/4"BSP	
	2-16	8-60			
	2-20	8-80			
DFC-25T	1.5-15	6-60	20-200 25-250	Male 1"NPT 1"BSP	
	3-13	10-50			
	4-24	10-100			
	5-35	10-130			
	5-45	10-170			

